



## STANDARD resin cup wheel

for stone

- + Very good stock removal rate
- + Very good lifetime
- + Best results on stone and short-chipping materials

DESIGNED FOR:



SUITABLE FOR:



### Varianten (5)


**Form 11BT**

3 Varianten

| Article No. | D / J x T x H        | Specification | VPE |
|-------------|----------------------|---------------|-----|
| 895670      | 110 / 90 x 55 x 22,2 | C 36 - B      | 2   |
| 895671      | 110 / 90 x 55 x 22,2 | C 60 - B      | 2   |
| 895679      | 110 / 90 x 55 x 22,2 | C 16 - B      | 2   |


**Form 11ZT**

2 Varianten

| Article No. | D / J x T x GE      | Specification | VPE |
|-------------|---------------------|---------------|-----|
| 895676      | 110 / 90 x 55 x M14 | C 16 - B      | 2   |
| 895677      | 110 / 90 x 55 x M14 | C60-B         | 2   |

### Description

Tyrolit STANDARD cup wheels achieve very good stock removal rates and lifetime for large-area grinding jobs. The cup wheel available for stone is particularly suitable for grinding scars on exposed concrete surfaces, bevelling and pre-grinding of engineered stone and terrazzo slabs as well as surface grinding on marble, slate and granite. For tool attachment you can choose between bore design 22, 23 and thread design M14. Please note the operating speed of max. 50 m/s.

### Features

- + Very good stock removal for grinding jobs on large areas
- + Robust and durable
- + Silicon carbide for outstanding results on stone and short-chipping materials

### Applications

- + For demanding applications on stone
- + For grinding imperfections on visible concrete surfaces, bevelling and pre-grinding artificial stone and patio flags as well as surface grinding on marble, slate and granite



[View online](#)

**Tyrolit AG**

Subject to technical changes • 07/04/2026